

ADVANTAGE

► Robust

built for heavy environmental conditions.

► Soft and crisp mode

multiple arc modes for different electrode types.

► Auto-adaptive arc force

Standard in Soft and Crisp modes the automatic variable Arc Force operates when it's required.

► Adjustable hot start control

allows a smooth start /restart of the electrode.

► Adjustable arc force control

manually adjusts the Arc Force to prevent sticking of the electrode in the weld pool.

► Anti-stick

automatically decreases the current to minimum if by error the electrode sticks to the work piece at any time.



Professional Welders for tough working conditions

The Inverter[®] 270SX and 400SX Stick and Lift TIG welders have been designed and manufactured to combine both a rugged industrial construction with excellent arc characteristics. Both machines are built to handle harsh environmental conditions using Lincoln tunnel technology to separate the PCBs and sensitive parts from contaminating cooling airflow. The robust metal case with large protective rubber corners makes these machines suitable for operation on site in conjunction with a generator, or within a workshop environment, providing maximum flexibility and durability.

Intensive and extensive testing in the Lincoln lab guarantees the quality of these welders.

Both units are equipped with features that will exceed the professional welder's expectations. The 270 and 400SX have two weld modes: Soft and Crisp as well as Adjustable Hot Start, Auto Adaptive Arc Force and Lift TIG.

Arc Force prevents sticking and shorting of the electrode during welding. Both machines allow manual adjustment but in Crisp or Soft mode Auto Adaptive Arc Force is employed which adjusts the arc force automatically.

Equipped with Anti Stick as standard preventing the electrode sticking on contact with the work piece by automatically switching the current down to minimum, preventing overheating of the electrode and further damage to equipment.

The machines are equipped with digital meters which display the pre-settable welding current, actual welding current or voltage during welding. The optional remote control allows fine adjustments during welding and the high duty cycle of these machines supports continuous welding with a wide variety of electrode types.

Invertec® 270SX – 400SX



IP testing in the Lincoln lab



Dust test



Final test of actual duty cycle, electrical safety, EMC

TECHNICAL SPECIFICATIONS

Product	Item Number	Primary Voltage	Fuse Size	Weight (kg)	Dimensions HxWxD (mm)	Protection/Insulation Class	Compliance
270SX	K12040-1	400V/3/50-60Hz +/-15%	20A	22	389 x 247 x 502	IP23 / H	EN60974-1 EN60974-10 CE ROHS
400SX	K12042-1		30A	37	455 x 301 x 632		


WELDING OUTPUT

Product	Current range	Input power	Rated output (40°C)	O.C.V.
270SX	5-270A	9.5kW @ 35% 6.3kW @ 100%	270A / 30.8V @ 35% 200A / 28V @ 100%	45Vdc
400SX	5-400A	10.9kW @ 35% 16.4kW @ 100%	400A / 36V @ 35% 300A / 32V @ 100%	


ACCESSORIES

Item Number	Description
KIT-250A-35-5M	Cable kit 250A, 35mm ² , 5m (270SX)
KIT-400A-70-5M	Cable kit 400A, 70mm ² , 5m (400SX)
K10095-1-15M	Control box, 1 potentiometer, 6 pins, 15m
K10398	Extension cable for remote control box, 15m
K10513-17-4V or -8V	TIG torch LT17 GV, 4m or 8m
W0200002	Undercarriage 270SX
K2694-1	Undercarriage 400SX

AUTO ADAPTATIVE ARC FORCE




Adjustable Arc Force



At the moment the Arc tended to short, the Amperage (B) increases to re-establish the Arc. The percentage extra weld current is adjustable.

Auto-adaptative Arc Force



The Arc voltage is measured continually to adapt the optimum value of Arc Force. This optimizes the Arc stability and minimizes spatter

Belgium:
Lincoln Smitweld Belgium
Tel: +32 54 33 42 12
e.mail: info@lincolnelectric.eu

Denmark:
Lincoln Electric Nordic
Tel: +45 86 26 51 00
e.mail: jtimmer@lincolnelectric.eu

Finland:
Lincoln Electric Nordic
Tel: +35 8 10 52235 00
e.mail: jtimmer@lincolnelectric.eu

France:
Lincoln Electric France
Tel: +33 2 32 11 40 40
e.mail: info@lincolnelectric.eu

Germany:
Lincoln Electric Deutschland
Tel: +49 2102 713960
e.mail: info@lincolnelectric.eu

Italy:
Lincoln Electric Italia
Tel: +39 010 754 111
e.mail: info@lincolnelectric.eu

The Netherlands:
Lincoln Smitweld
Tel: +31 24 3522 911
e.mail: info@lincolnelectric.eu

Norway:
Sveiseeksperten AS
Tel: +47 22 08 00 94
e.mail: info@lincolnelectric.eu

Poland:
Lincoln Electric Bester
Tel: +48 74 64 61 100
e.mail: info@lincolnelectric.eu

Portugal:
Electro Arco
Tel: +351 21 238 7300

Russia:
Lincoln Electric Russia
Tel: +7 (495) 6609404
e.mail: russia@lincolnelectric.eu

Spain:
Lincoln Electric Spain
Tel: +34 93 685 96 00
e.mail: info@lincolnelectric.eu

Sweden:
Svetskompaniet AB
Tel: +46 (0) 320 211710
e.mail: info@lincolnelectric.eu

UK/ Ireland:
Lincoln Electric UK
Tel: +44 114 287 2401
e.mail: info@lincolnelectric.eu